



0-420-12- 21.5" Driving Worklamp Bar with Position and Amber Warning

Durite Worklight 21.5" Driving Lamp with Amber Warning LED's and Position Lamp. 12/24V.200W OSRAM LED, 16,800 Lumens (5551 Effective). 1703LUX at 10M. 5700k Colour Temperature. IP68/IP69k. PCLens, Aluminium Housing, SS304 Brackets. 60cm Fly Lead with 6PIN DT Connector. Size: 560.6*70*67.3mm. EMarked R10(EMC), R7 (DRL), R112(Driving) and R65 (Warning).

Fly Leads:

- Red = Main Driving Light
- Black = Negative -VE
- Grey = White Position Light
- Yellow = Amber Warning Light
- Green = Amber Position Light

THE TRUSTED QUALITY BRAND FOR PROFESSIONALS



TECHNICAL SPECIFICATIONS

Type	Worklight Driving Lamp with Position / Amber Warning
Voltage	10-30VDC
LED's	Driving: 40 x 5W OSRAM LED, Pos30 LED's Amber 40 LED's
Power	Driving: 84W, Pos1W, Warning 11W Amber
Current Draw	Driving 6.5A at 12V. Pos0.15A at 12V, Warning 0.77A at 12V
Lumens/ Lux	16,800 (5551 Effective). 1703LUX at 10M
IP Rating	IP68 / IP69K
Material Construction	Aluminium with PC Lens. Bracket SS304
Weight	2.355Kg
Dimensions	560.6*70*67.3mm
Operating Temperature	-30°C to +65°C
Storage Temperature	-40°C to +85°C
Certificate	CE, E Mark R10, R7, R65, R112

TECHNICAL DRAWING

